


DETAIL & SUBMITTAL SHEET

by Bilco



FRONT ELEVATION



SPECIFICATIONS:

Material: Cover and frame are 1/4" steel

Cover: Diamond-pattern tread plate reinforced for 300 psf (1464 kg/m²) live load

Frame: Formed channel frame with full anchor angle welded around the perimeter. A 1-1/2" drain coupling is welded under the frame for a pipe connection to a dry well or disposal system.

Hinges: Heavy forged brass hinges with 3/8" Type 316 stainless steel hinge pins


Latch: Type 316 stainless steel slam lock with fixed interior handle and removable exterior turn/lift handle. Latch release is protected by a flush, gasketed, removable screw plug

Lift Assistance: Compression spring operators enclosed in telescopic tubes. Automatic hold-open arm with grip handle release.

Finish: Alkyd base red oxide primer

Hardware: Engineered composite compression spring tubes. Steel compression springs with electrocoated acrylic finish. Slam lock and all fasteners are Type 316 stainless steel. All other hardware is zinc plated/chromate sealed.

SECTION DETAIL



✓	Item No.	Door Opening W x H	Material	Ship Wt. Lbs.
	J 1	24 x 24	Steel	50
	J 2	30 x 30	Steel	65
	J 3	36 x 30	Steel	77
	J 4	36 x 36	Steel	86
	J 5	42 x 42	Steel	109

JD available upon request (double leaf)

Project: _____ Date: _____

Contractor: _____ Architect: _____

Sizes: _____ Quantity: _____ Approval Initials: _____



Corporate Office: 1330 Progress Drive • Front Royal, VA 22630
Phone: 1-800-255-5515 • Fax: 1-800-822-5001

www.wbdoors.com